



AUTOPOINTING ANTENNAS

RF FORMANCE AND POINTING
CHARACTERISATION BY EUTELSAT

23 January 2020

Table of Contents

Autopointing Antennas	2
Introduction	3
AKD	16
1.25m x 1.35m - AKD-V12U	16
C-COM	11
1.2m - iNetVu 1201	11
COBHAM (Tracstar - Cobham)	13
1.0m - Explorer 7100 MB Ku	13
DATAPATH	20
2m x 1.6m - CCT200 Fly-Away	20
HITACHI (PALS)	17
1.5m x 1.35m PDA 150 Drive News	17
HOLKIRK	12
1.5 m - RM150	12
ND SATCOM	4
1.5m - SkyRAY MAS 1900	5
PROSAT	7
1.2m - D120M	7
1.5m - D150M	8
SATMISSION	18
1.20m x 1.25m SMP 125 DA	19
1.54m x 1.39m SMP 155 DA	18
SVS	9
1.2m - SDC120	9
1.5m - SDC150	10
THRANE & THRANE (COBHAM)	14
1m Explorer 6100	21
1m Explorer 8100	14
1.2m Explorer 8120	15
VISLINK	6
1.2m - FlyDrive 120	6
ANNEX 1	22

EARTH STATION ANTENNAS AUTO-POINTING CHARACTERISATION BY EUTELSAT

GENERAL

This list aims at providing Eutelsat customers with guidance on the selection of the most appropriate earth station equipment capable of automatically point and peak the antenna to Eutelsat Fleet, without need of expert operators.

We underline that the auto-pointing systems which are listed in this document have been characterised in regard of the Eutelsat criteria, but that **the Earth station operations and space segment access remain subject to application of procedures as per ESOG 140.**

Prior an access to the Eutelsat Fleet, each Earth station using one of these systems has to be applied for to the Earth Station Approval Office, as per indicated in the ESOG 110, and individually approved.

The criteria for inclusion are:

- Eutelsat is in possession of a full set of measured RF electrical characteristics,
- The antenna's RF performance fully meets the minimum Eutelsat requirements (EESS 502) at the characterisation's date.
- There is no known record of operational problems or interference issues related to this antenna,
- Auto-pointing performance has been validated repeatedly on at least three different satellites of the Eutelsat fleet.
- Use of VSAT reflectors is not encouraged, unless proven demonstration of manufacturing high quality processes and performance repeatability

Inclusion in the list is a decision which pertains uniquely and ultimately to Eutelsat alone. At any moment a given antenna may be removed from the list, should Eutelsat deem necessary to do so, for operational reasons.

Notes:

- The characterisation's validity is subject to regular submission of patterns to confirm that the system remains compliant with the Eutelsat standard at the inspection date.
- Any change to the characterised configuration need to be notified to Eutelsat and may be subject to further tests.
- Transmissions in the 13.75 GHz to 14.00 GHz frequency band are subject to additional constraints imposed by the Radio Regulations. Antennas with diameters <1.2m are not supposed to operate in the 13.75 to 14.00 GHz frequency band.
- The information which is provided in this book is relative to the dynamic antenna systems performance. Their static performance are shown on the following links:

<http://www.eutelsat.com/files/contributed/satellites/pdf/typeapproval.pdf>

http://www.eutelsat.com/files/contributed/support/pdf/RF_Characterisation.pdf

**Applicant:**

ND SatCom GmbH
P.O. Box
88039 Friedrichshafen
GERMANY
Tel : +49 7545 939 8725
Fax : +49 7545 939 8866

Website : www.ndsatcom.com
Email : christian.hauff@ndsatcom.com

Antenna model:

SkyRAY Compact 1500
SkyRAY Compact 1500 Plus
SkyRAY MAS 1500

Diameter:

1.2 m
(See Remark 4)

Standard:

M

Characterisation date:

01-06-2011

Validity period:

See Remark 6

System Description:

Auto-pointing system based on the ERA type approved EA-A017 one piece 1.2 m Ku diamond shape offset antenna with mode generator, vehicle mounted, working with ND SatCom antenna controller ACU 4100 or ACU 5020 series and either a ND SatCom SkyWAN modem or a commercial IRD Tandberg TT1260 or equivalent as pointing device.

Maximum Allowed EIRP:

35.2 dBW / 4 kHz for digital carriers transmitted at the satellite receive contour of 0 dB/K (EESS 502 § 6.1 refers)

Tx Frequency:

13.75 - 14.50 GHz

Rx Frequency:

10.95 - 12.75 GHz

Pointing error:

Azimuth and Elevation $\leq 0.1^\circ$

Polarisation $\leq 2.1^\circ$

Tx XPD:

>27 dB within -1 dB contour

Rx XPD:

>27 dB within -1 dB contour

Remarks:

- 1 Tests have been performed via satellite with the ERS of Aflenz on the 23rd August 2010.
- 2 The system has been validated with two different Eutelsat satellites, both with an angle of the polarisation plane equal to 3.5°.
- 3 Transmission cannot be authorised until the peaking process is completed.
- 4 The dimensions of the Ku Diamond antennas are 1.5mx1.5m, the equivalent circular diameter is 1.2m
- 5 SkyRAY MAS/Compact 1500 is equipped with one HPA (400 Watt maximum), SkyRAY Compact 1500 Plus is equipped with two HPAs (400 Watt maximum for each).
- 6 The characterisation's validity is subject to regular submission of patterns to confirm that the system remains compliant with the Eutelsat standard at the inspection date.
- 7 Any change to the characterised configuration need to be notified to Eutelsat and may be subject to further tests.

**Applicant:**

ND SatCom GmbH
P.O. Box
88039 Friedrichshafen
GERMANY
Tel : +49 7545 939 8725
Fax : +49 7545 939 8866

Website : www.ndsatcom.com
Email : christian.hauff@ndsatcom.com

Antenna model:

SkyRAY MAS 1900

Diameter:

1.5 m

(See Remark 4)

Standard:

M

Characterisation date:

01-08-2011

Validity period:

See Remark 6

System Description:

Auto-pointing system based on the ERA type approved EA-A004 one piece 1.5 m Ku diamond shape offset antenna with mode generator, vehicle mounted, working with ND SatCom antenna controller ACU 5020 series and either a ND SatCom SkyWAN modem or a commercial IRD Tandberg Rx1290 or equivalent as pointing device.

Maximum Allowed EIRP:

35.7 dBW / 4 kHz for digital carriers transmitted at the satellite receive contour of 0 dB/K (EESS 502 § 6.1 refers)

Tx Frequency:

13.75 - 14.50 GHz

Rx Frequency:

10.95 - 12.75 GHz

Pointing error:

Azimuth and Elevation $\leq 0.16^\circ$

Polarisation $\leq 2.0^\circ$

G/T:

23.9 dB/K @12.661 GHz for 35° Elevation

Tx XPD:

>27.8 dB within -1 dB contour

>30.0 dB within the de-pointing angle

Rx XPD:

Not measured

Remarks:

- 1 Tests have been performed via satellite with the ERS of Aflenz on the 30th June and 1st July 2011.
- 2 The system has been validated with three different Eutelsat satellites, with angles of the polarisation plane equal to either 0° or 3.5°.
- 3 Transmission cannot be authorized until the peaking process is completed.
- 4 The dimensions of the Ku Diamond antennas are 1.9mx1.9m; the equivalent circular diameter is 1.5m
- 5 SkyRAY MAS1900 can be equipped with one HPA (750 Watt maximum) or with two HPA's (750 Watt maximum for each). The tests were performed on a configuration with two HPAs of 400 W mounted on the back frame of the antenna.
- 6 The characterisation's validity is subject to regular submission of patterns to confirm that the system remains compliant with the Eutelsat standard at the inspection date.
- 7 Any change to the characterised configuration need to be notified to Eutelsat and may be subject to further tests.

Eutelsat s.A. Auto-Pointing Summary Sheet



Applicant:

VISLINK Communications Ltd
27 Maylands Avenue
Hemel Hempstead
Hertfordshire, HP2 7DE
United Kingdom
Tel :+ 44 (0) 1442 431 300
Fax :+44 (0) 1442 431 301

Website : www.vislink.com
Email : Dave.melville@vislink.com

Antenna model:

FlyDrive 120

Diameter:
1.2 m

Standard:
M

Characterization date:
23-11-2011

Validity period:
See remark 5

System Description:

Auto-pointing system based on the Advent four segments 1.2 m Ku antenna with mode generator, for Fly away and Drive Away applications, working with Advent antenna controller ACU 5000 series and Advent Lynx 5100 Video Exciter/IRD.

Maximum Allowed EIRP:

45 dBW/40 kHz for digital carriers transmitted at the satellite receive contour of 0 dB/K (EESS 502 § 6.1 refers)

Tx Frequency:

13.75 - 14.50 GHz

Rx Frequency:

10.70 - 12.75 GHz

Pointing error:

Azimuth and Elevation $\leq 0.3^\circ$
Polarisation $\leq 1.1^\circ$

G/T:

17.7 dB/K @11.121 GHz for 30° Elevation

Tx XPD:

>33.8 dB at boresight
>32.0 dB within -1 dB contour

Rx XPD:

>23.4 dB within -1 dB contour

Remarks:

- 1 Tests have been performed via satellite with the ERS of Aflenz on the 22 and 23 August 2011.
- 2 The system has been validated with three different Eutelsat satellites, with angles of the polarisation plane equal to 3.5°.
- 3 Transmission cannot be authorized until the peaking process is completed.
- 4 FlyDrive 120 can be equipped with one HPA (400 Watt maximum).
- 5 The characterisation's validity is subject to regular submission of patterns to confirm that the system remains compliant with the Eutelsat standard at the inspection date.
- 6 Any change to the characterised configuration need to be notified to Eutelsat and may be subject to further tests.

Eutelsat s.A. Auto-Pointing Summary Sheet



Applicant:

PROSAT SOLUTIONS GMBH
Alfred-Nobel-Str. 5
55411 Bingen
GERMANY

Tel : +49 (0)6721 4008-0
Fax : +49 (0)6721 4008-27

Website : <http://www.prosat-solutions.de>
Email : Peter.Jakobsson@prosat-solutions.de

Antenna model:

D120M

Diameter:

1.2 m

(See Remark 4)

Standard:

M

Characterisation date:

20-04-2012

Validity period:

See Remark 6

System Description:

Auto-pointing system based on the CTS ERA type approved EA-A017 one piece 1.2 m Ku Diamond shape front fed offset antenna with mode generator, vehicle mounted, working with ProSat antenna controller AKS200A series.

Maximum Allowed EIRP for digital carriers transmitted at the satellite receive contour of 0 dB/K (EESS 502 § 6.1 refers):

45.6 dBW / 40 KHz for an orbital separation of the adjacent satellite $\geq 2.0^\circ$

39.7 dBW / 40 KHz for an orbital separation of the adjacent satellite $\geq 1.5^\circ$

Tx Frequency:

13.75 - 14.50 GHz

Rx Frequency:

10.70 - 12.75 GHz

Pointing error:

Azimuth and Elevation $\leq 0.2^\circ$

Polarisation $\leq 0.7^\circ$

G/T:

22.0 dB/K @10.95 GHz for 42° Elevation

Tx XPD:

>35 dB within -1 dB contour

Rx XPD:

Not measured

Remarks:

- 1 Tests have been performed via satellite with the ERS of Aflenz on the 1-2 March 2012.
- 2 The system has been validated with four different Eutelsat satellites, with angles of the polarisation plane equal to either 0° or 3.5° .
- 3 Transmission cannot be authorized until the peaking process is completed.
- 4 The physical dimensions of the Ku Diamond antennas are H1.52m x V1.36m.
- 5 D120M is equipped with one or two 1:1 redundant HPAs (400 Watt maximum).
- 6 The characterisation's validity is subject to regular submission of patterns to confirm that the system remains compliant with the Eutelsat standard at the inspection date.
- 7 Any change to the characterised configuration need to be notified to Eutelsat and may be subject to further tests.

Eutelsat s.A. Auto-Pointing Summary Sheet



Applicant:

PROSAT SOLUTIONS GMBH
Alfred-Nobel-Str. 5
55411 Bingen
GERMANY

Tel : +49 (0)6721 4008-0
Fax : +49 (0)6721 4008-27

Website : <http://www.prosat-solutions.de>
Email : Peter.Jakobsson@prosat-solutions.de

Antenna model:

D150M

Diameter:

1.5 m

(See Remark 4)

Standard:

M

Characterisation date:

20-04-2012

Validity period:

See Remark 6

System Description:

Auto-pointing system based on the CTS ERA type approved EA-A004 one piece 1.5 m Ku Diamond shape front fed offset antenna with mode generator, vehicle mounted, working with ProSat antenna controller AKS200A series.

Maximum Allowed EIRP for digital carriers transmitted at the satellite receive contour of 0 dB/K (EESS 502 § 6.1 refers):

37.0 dBW / 4 KHz for an orbital separation of the adjacent satellite $\geq 2.0^\circ$

44.9 dBW / 40 KHz for an orbital separation of the adjacent satellite $\geq 1.5^\circ$

Tx Frequency:

13.75 - 14.50 GHz

Rx Frequency:

10.70 - 12.75 GHz

Pointing error:

Azimuth and Elevation $\leq 0.2^\circ$

Polarisation $\leq 1.2^\circ$

G/T:

22.6 dB/K @10.95 GHz for 42° Elevation

Tx XPD:

>30 dB within -1 dB contour

Rx XPD:

Not measured

Remarks:

- 1 Tests have been performed via satellite with the ERS of Aflenz on the 23-26 January 2012.
- 2 The system has been validated with three different Eutelsat satellites, with angles of the polarisation plane equal to 3.5°.
- 3 Transmission cannot be authorized until the peaking process is completed.
- 4 The physical dimensions of the Ku Diamond antennas are H1.89m x V1.695m.
- 5 D150M is equipped with one or two 1:1 redundant HPAs (400 Watt maximum).
- 6 The characterisation's validity is subject to regular submission of patterns to confirm that the system remains compliant with the Eutelsat standard at the inspection date.
- 7 Any change to the characterised configuration need to be notified to Eutelsat and may be subject to further tests.

Eutelsat s.A. Auto-Pointing Summary Sheet



Applicant:

SVS SATELLITE SYSTEMS
Esenkent Mahallesi Baraj Yolu Caddesi
Emirgan Sokak No:3
34776 Umraniye/ISTANBUL
TURKEY

Tel : +90 216 329 56 00
Fax : +90 216 329 02 99

Website : <http://www.svstelekom.com.tr>
Email : abdullah.saglam@svstelekom.com.tr

Antenna model:

SVS SDC120

Diameter:

1.2 m

(See Remark 4)

Standard:

M

Characterisation date:

20-04-2012

Validity period:

See Remark 6

System Description:

Auto-pointing system based on the CTS ERA type approved EA-A017 one piece 1.2 m Ku Diamond shape front fed offset antenna with mode generator, vehicle mounted, working with SVS antenna controller AKS200A series.

Maximum Allowed EIRP for digital carriers transmitted at the satellite receive contour of 0 dB/K (EESS 502 § 6.1 refers):

45.6 dBW / 40 KHz for an orbital separation of the adjacent satellite $\geq 2.0^\circ$

39.7 dBW / 40 KHz for an orbital separation of the adjacent satellite $\geq 1.5^\circ$

Tx Frequency:

13.75 - 14.50 GHz

Rx Frequency:

10.70 - 12.75 GHz

Pointing error:

Azimuth and Elevation $\leq 0.2^\circ$

Polarisation $\leq 0.7^\circ$

G/T:

22.0 dB/K @10.95 GHz for 42° Elevation

Tx XPD:

>35 dB within -1 dB contour

Rx XPD:

Not measured

Remarks:

- 1 Tests have been performed via satellite with the ERS of Aflenz on the 1-2 March 2012.
- 2 The system has been validated with four different Eutelsat satellites, with angles of the polarisation plane equal to either 0° or 3.5° .
- 3 Transmission cannot be authorized until the peaking process is completed.
- 4 The physical dimensions of the Ku Diamond antennas are H1.52m x V1.36m.
- 5 SVS SDC 120 is equipped with one or two 1:1 redundant HPAs (400 Watt maximum).
- 6 The characterisation's validity is subject to regular submission of patterns to confirm that the system remains compliant with the Eutelsat standard at the inspection date.
- 7 Any change to the characterised configuration need to be notified to Eutelsat and may be subject to further tests.

Eutelsat s.A. Auto-Pointing Summary Sheet



Applicant:

SVS SATELLITE SYSTEMS
Esenkent Mahallesi Baraj Yolu Caddesi
Emirgan Sokak No:3
34776 Umraniye/ISTANBUL
TURKEY

Tel : +90 216 329 56 00
Fax : +90 216 329 02 99

Website : <http://www.svstelekom.com.tr>
Email : abdullah.saglam@svstelekom.com.tr

Antenna model:

SVS SDC150

Diameter:

1.5 m

(See Remark 4)

Standard:

M

Characterisation date:

20-04-2012

Validity period:

See Remark 6

System Description:

Auto-pointing system based on the CTS ERA type approved EA-A004 one piece 1.5 m Ku Diamond shape front fed offset antenna with mode generator, vehicle mounted, working with SVS antenna controller AKS200A series.

Maximum Allowed EIRP for digital carriers transmitted at the satellite receive contour of 0 dB/K (EESS 502 § 6.1 refers):

37.0 dBW / 4 KHz for an orbital separation of the adjacent satellite $\geq 2.0^\circ$

44.9 dBW / 40 KHz for an orbital separation of the adjacent satellite $\geq 1.5^\circ$

Tx Frequency:

13.75 - 14.50 GHz

Rx Frequency:

10.70 - 12.75 GHz

Pointing error:

Azimuth and Elevation $\leq 0.2^\circ$

Polarisation $\leq 1.2^\circ$

G/T:

22.6 dB/K @10.95 GHz for 42° Elevation

Tx XPD:

>30 dB within -1 dB contour

Rx XPD:

Not measured

Remarks:

- 1 Tests have been performed via satellite with the ERS of Aflenz on the 23-26 January 2012.
- 2 The system has been validated with three different Eutelsat satellites, with angles of the polarisation plane equal to 3.5°.
- 3 Transmission cannot be authorized until the peaking process is completed.
- 4 The physical dimensions of the Ku Diamond antennas are H1.89m x V1.695m.
- 5 SVS SDC 150 is equipped with one or two 1:1 redundant HPAs (400 Watt maximum).
- 6 The characterisation's validity is subject to regular submission of patterns to confirm that the system remains compliant with the Eutelsat standard at the inspection date.
- 7 Any change to the characterised configuration need to be notified to Eutelsat and may be subject to further tests.

Eutelsat s.A. Auto-Pointing Summary Sheet



C-COM Satellite Systems Inc.
2574 Sheffield Rd,
Ottawa ON,
K1B 3V7
Canada
Tel: +1 613 745 4110
Fax: +1 613 745 7144

Website : <http://www.c-comsat.com>
mailto: bawada@c-comsat.com

Antenna model:
C-COM iNetVu 1201

Diameter:
1.2 m
2-ports feed
(See Remark 4)

Standard:
M

Characterisation date:
03-05-2012

Validity period:
See Remark 6

System Description:

Auto-pointing antenna system based on the Skyware Global 125 single piece 1.2 m SMC reflector. Front fed offset configuration with mode generator and rotary joint. Two ports die-cast OMT, linear polarization.

HPA maximum permissible rating: 40 Watt.

Maximum Allowed EIRP:

42.0 dBW / 40 KHz for an orbital separation of the adjacent satellite > 2.0°

37.1 dBW / 40 kHz for an orbital separation of the adjacent satellite > 1.5°

for digital carriers transmitted at the satellite receive contour of 0 dB/K (EESS 502 § 6.1 refers).

Tx Frequency:
14.00-14.50 GHz

Rx Frequency:
10.70-12.75 GHz

Pointing error:
< 0.4°

Polarization error:
< 1.4°

Tx XPD:
>25 dB within -1 dB contour

Rx XPD:
Not measured

Remarks:

- 1 Tests have been performed via satellite with the ERS of Aflenz on the 26-27 March 2013.
- 2 The system has been validated with three different Eutelsat satellites, with angles of the polarization plane equal to 3.5°.
- 3 Transmission cannot be authorized until the peaking process is completed.
- 4 The physical dimensions of Skyware Global 125 antennas are H1.23m x V1.37m.
- 5 Installation of HPA with a power >40 W is not authorized.
- 6 The characterisation's validity is subject to regular submission of patterns to confirm that the system remains compliant with the Eutelsat standard at the inspection date.
- 7 Any change to the characterised configuration need to be notified to Eutelsat and may be subject to further tests.
- 8 The maximum tilt angle of the antenna when in operations is limited to angles <10°.

Eutelsat s.A. Auto-Pointing Summary Sheet

**Manufacturer:**

Holkirk Communications Ltd
Unit 17 Pulloxhill Business Park
Greenfield Road
Bedfordshire
United Kingdom
MK45 5EU

Tel: +44 (0) 1525 721118
Fax: +44 (0) 1525 719734
Email bob@holkirk.com
Web www.holkirk.com

Antenna model:
RM150

Diameter:
1.5 m

Standard:
M

Characterisation date:
05-07-2012

Validity period:
See Remark 5

System Description:

Auto-pointing antenna system based on the Holkirk single piece 1.5 m Ku reflector. Front fed offset configuration with mode generator and rotary joint.

For drive away applications with HPA maximum permissible rating of 400 Watt.

Maximum Allowed EIRP:

45.1 dBW / 40 KHz for an orbital separation of the adjacent satellite $\geq 2.5^\circ$

41.6 dBW / 40 KHz for an orbital separation of the adjacent satellite $\geq 2.0^\circ$

40.6 dBW / 40 kHz for an orbital separation of the adjacent satellite $\geq 1.5^\circ$

for digital carriers transmitted at the satellite receive contour of 0 dB/K (EESS 502 § 6.1 refers).

Tx Frequency:
13.75-14.50 GHz

Rx Frequency:
10.70-12.75 GHz

Pointing error:
< 0.2°

Polarization error:
< 1.5°

Tx XPD:
 ≥ 30 dB within -1 dB contour

Rx XPD:
Not measured

Remarks:

- 1 Tests have been performed via satellite with the ERS of Aflenz on the 21-22 May 2013.
- 2 The system has been validated with three different Eutelsat satellites, with angles of the polarization plane equal to 3.5°.
- 3 Transmission cannot be authorized until the peaking process is completed.
- 4 Installation of HPAs with a power up to 400 Watt is authorized.
- 5 The characterisation's validity is subject to regular submission of patterns to confirm that the system remains compliant with the Eutelsat standard at the inspection date.
- 6 Any change to the characterised configuration need to be notified to Eutelsat and may be subject to further tests.
- 7 The maximum tilt angle of the antenna when in operations is limited to angles $\leq 10^\circ$.

Eutelsat s.A. Auto-Pointing Summary Sheet

**Manufacturer:**

TRACSTAR SYSTEMS INC.
COBHAM ANTENNA SATCOM LAND SYSTEMS
1551 College Park Business Center Rd.,
Orlando, FL 32804 USA.

Tel: + 1 407 650 9054

Fax: + 1 407 650 9086

Website: <http://www.cobham.com/satcom>

mailto: Narcis.Vila@cobham.com or

Jackie.Rubie@cobham.com

Antenna model:

Cobham EXPLORER 7100 MB KU

Diameter:

1 m

Standard:

M

Characterisation date:

18-02-2014

Validity period:

See Remark 5

System Description:

Auto-pointing antenna system based on the AVL 1080KVH model, single piece 1.0 m reflector and TracStar controller. Front fed offset configuration.

For drive away applications with HPA maximum permissible rating of 40 W.

Maximum Allowed EIRP:

43.9 dBW / 40 KHz for an orbital separation of the adjacent satellite $\geq 2.5^\circ$

42.4 dBW / 40 KHz for an orbital separation of the adjacent satellite $\geq 2.0^\circ$

37.0 dBW / 40 KHz for an orbital separation of the adjacent satellite $\geq 1.5^\circ$

for digital carriers transmitted at the satellite receive contour of 0 dB/K (EESS 502 § 6.1 refers)

Tx Frequency:

13.75-14.50 GHz

Rx Frequency:

10.70-12.75 GHz

Pointing error:

$\leq 0.4^\circ$

Polarisation error:

$< 1.2^\circ$

Tx XPD:

≥ 25 dB within -1 dB contour

Rx XPD:

Not measured

Remarks:

- 1 Tests have been performed via satellite with the ERS of Aflenz on the 18-19 November 2013.
- 2 The system has been validated with three different Eutelsat satellites, with angles of the polarisation plane equal to 3.5° . Satellite reference mode has been tested.
- 3 Transmission is not authorised until the peaking process is completed.
- 4 The Explorer 7100 is authorised for operations with one HPA up to 40 Watt maximum. Irrespective of their installed power rating, Cobham certifies that all HPAs being used with this antenna configuration are equipped with M&C and EIRP readout capabilities
- 5 The characterisation's validity is subject to regular submission of patterns to confirm that the system remains compliant with the Eutelsat standard at the inspection date.
- 6 Any change to the characterised configuration need to be notified to Eutelsat and may be subject to further tests.
- 7 The maximum tilt angle of the antenna when in operations is limited to angles $< 10^\circ$. To ensure successful operations in tilt conditions, a tilt calibration procedure has to be performed in factory for each unit manufactured.

Eutelsat s.A. Auto-Pointing Summary Sheet

**Applicant:**

THRANE & THRANE A/S trading as COBHAM
SATCOM
Lundtoftegaardsvej 93D, 2800 Kgs.
Lyngby
DENMARK

Tel : +45 39 55 89 59

Website : www.cobham.com

Email : info@cobham.com

Antenna model:
EXPLORER 8100

Diameter:
1.0 m

Standard:
M

Characterization date:
23-02-2017

Validity period:
See remark 5

Last test data submitted on:
23-02-2017

System Description:

Antenna system based on a single piece carbon fibre reflector, front fed offset 1.0 m Ku antenna, with two port linear polarization feed, manufactured by Thrane & Thrane A/S trading as Cobham Satcom, for drive-away applications, with HPA maximum permissible rating as per remark 4.

Maximum Allowed EIRP: For digital carriers transmitted at the satellite receive contour of 0 dB/K (EESS 502 refers):

In the 14.00 - 14.50 GHz band:

36.1 dBW / 40 kHz for an orbital separation from the adjacent satellite $\geq 1.5^\circ$

39.8 dBW / 40 kHz for an orbital separation from the adjacent satellite $> 2.0^\circ$

43.4 dBW / 40 kHz for an orbital separation from the adjacent satellite $> 2.5^\circ$

In the 13.75 - 14.00 GHz band:

34.2 dBW / 40 kHz for an orbital separation from the adjacent satellite $\geq 1.5^\circ$

37.7 dBW / 40 kHz for an orbital separation from the adjacent satellite $> 2.0^\circ$

41.0 dBW / 40 kHz for an orbital separation from the adjacent satellite $> 2.5^\circ$

Tx Frequency:

13.75 - 14.50 GHz

Rx Frequency:

10.70 - 12.75 GHz

Pointing error:

$\leq 0.1^\circ$

Polarization error:

$< 1.2^\circ$

Tx XPD:

≥ 30.1 dB within $\pm 0.1^\circ$ de-pointing angle

Rx XPD:

≥ 23.6 dB within -1 dB contour

≥ 29.5 dB within $\pm 0.1^\circ$ de-pointing angle
with auto-pointing option

Remarks:

- 1 Auto-pointing tests were performed via satellite from Lyngby with the ERS of Aflenz on the 25-27 January 2017. RF performance tests were performed on one antenna unit at the Thales Alenia Space test range of Cannes, France on the 20 February 2017.
- 2 The EXPLORER ACU auto-pointing system has been validated with three different Eutelsat satellites, with angles of the polarization plane equal to 3.5° .
- 3 Transmission is not authorized until the peaking process is completed.
- 4 The EXPLORER 8100 comes in three standard configurations: No BUC, 8 and 20W BUC. Installation of HPAs with a power >50 W is not authorized
- 5 The characterisation's validity is subject to regular submission of patterns to confirm that the system remains compliant with the Eutelsat standard at the inspection date.
- 6 Any change to the characterised configuration need to be notified to Eutelsat and may be subject to further tests.

**Applicant:**

THRANE & THRANE A/S trading as COBHAM
SATCOM
Lundtoftegaardsvej 93D, 2800 Kgs.
Lyngby
DENMARK

Tel : +45 39 55 89 59

Website : www.cobham.com

Email : info@cobham.com

Antenna model:
EXPLORER 8120

Diameter:
1.2 m

Standard:
M

Characterization date:
23-02-2017

Validity period:
See remark 5

Last test data submitted on:
23-02-2017

System Description:

Antenna system based on a single piece carbon fibre reflector, front fed offset 1.2 m Ku antenna, with two port linear polarization feed, manufactured by Thrane & Thrane A/S trading as Cobham Satcom, for drive-away applications, with HPA maximum permissible rating as per remark 4.

Maximum Allowed EIRP: For digital carriers transmitted at the satellite receive contour of 0 dB/K (EESS 502 refers):

In the 14.00-14.50 GHz band:

39.1 dBW / 40 kHz for an orbital separation from the adjacent satellite $\geq 1.5^\circ$

34.6 dBW / 4 kHz (equivalent to 44.6 dBW/40 KHz) for an orbital separation from the adjacent satellite $> 2.0^\circ$

In the 13.75-14.00 GHz band:

36.3 dBW / 40 kHz for an orbital separation from the adjacent satellite $\geq 1.5^\circ$

42.4 dBW / 40 kHz for an orbital separation from the adjacent satellite $> 2.0^\circ$

Tx Frequency:

13.75 - 14.50 GHz

Rx Frequency:

10.70 - 12.75 GHz

Pointing error:

$\leq 0.1^\circ$

Polarization error:

$< 1.0^\circ$

Tx XPD:

≥ 32.6 dB within $\pm 0.1^\circ$ de-pointing angle

Rx XPD:

≥ 26.9 dB within -1 dB contour

≥ 37.9 dB within $\pm 0.1^\circ$ de-pointing angle
with auto-pointing option

Remarks:

- 1 Auto-pointing tests were performed via satellite from Lyngby with the ERS of Aflenz on the 25-27 January 2017. RF performance tests were performed on one antenna unit at the Thales Alenia Space test range of Cannes, France on the 21 February 2017.
- 2 The EXPLORER ACU system has been validated with three different Eutelsat satellites, with angles of the polarization plane equal to 3.5° .
- 3 Transmission is not authorized until the peaking process is completed.
- 4 The EXPLORER 8120 comes in three standard configurations: No BUC, 8 and 20W BUC. Installation of HPAs with a power >50 W is not authorized
- 5 The characterisation's validity is subject to regular submission of patterns to confirm that the system remains compliant with the Eutelsat standard at the inspection date.
- 6 Any change to the characterised configuration need to be notified to Eutelsat and may be subject to further tests.

**Applicant:**

AKD Communication Technology Co.,Ltd
3F, Building A, No. 7 Haiying Road, Fengtai Science
City, Beijing 100070, China

Website : <http://www.akdtech.com.cn/en/>

Email : kgao@akdtech.com.cn

Antenna model:

AKD-V12U

Antenna aperture dimensions:

1.25m H x 1.35m V

Standard:

M

Characterization date:

11-04-2017

Validity period:

See remark 5

Last test data submitted on:

15-05-2017

System Description:

Antenna system based on a single piece SMC reflector, front fed offset, 1.25 m equivalent circular Ku antenna, with two port linear polarization feed, manufactured by AKD Communication Technology Co.,Ltd, for drive-away applications, with HPA maximum permissible rating as per remark 4. The detail of the characterization of the antenna system with an auto-pointing configuration is available via the following link: http://www.eutelsat.com/files/contributed/satellites/pdf/Autopointing_Antennas.pdf

Maximum Allowed EIRP: For digital carriers transmitted at the satellite receive contour of 0 dB/K (EESS 502 refers):

In the 14.00-14.50 GHz band:

37.9 dBW / 40 kHz for an orbital separation from the adjacent satellite $\geq 1.5^\circ$

42.5 dBW / 40 kHz for an orbital separation from the adjacent satellite $> 2.0^\circ$

44.7 dBW / 40 kHz for an orbital separation from the adjacent satellite $> 2.5^\circ$

In the 13.75-14.00 GHz band:

36.1 dBW / 40 kHz for an orbital separation from the adjacent satellite $\geq 1.5^\circ$

40.6 dBW / 40 kHz for an orbital separation from the adjacent satellite $> 2.0^\circ$

40.8 dBW / 40 kHz for an orbital separation from the adjacent satellite $> 2.5^\circ$

Tx Frequency:

13.75 - 14.50 GHz

Rx Frequency:

10.70 - 12.75 GHz

Tx Gain:

43.6 dBi (average at 14.25 GHz)

Rx Gain:

41.2 dBi (average at 11.70 GHz)

Tx XPD:

≥ 26.6 dB within -1 dB contour

Rx XPD:

≥ 23.7 dB within -1 dB contour

G/T:

21.3 dB/K typ @ 11.70 GHz at 30° EI

Restrictions and remarks:

- 1 The authorization to operate the terminal is conditioned to the approval to access the Eutelsat S.A. Space Segment (ref. <http://www.eutelsat.com/files/contributed/satellites/pdf/esog110.pdf>, ESOG 110).
- 2 RF performance tests were performed on one antenna unit at the Catapult test range of Harwell, UK on 28 February and 1 March 2017.
- 3 Please refer to the following link for auto-pointing configuration details: http://www.eutelsat.com/files/contributed/satellites/pdf/Autopointing_Antennas.pdf
- 4 Installation of HPAs with a power >50 W is not authorized.
- 5 This Summary's validity is subject to regular submission of patterns to confirm that the system remains compliant with measured performance at the inspection date.
- 6 Any change to this configuration needs to be notified to Eutelsat and may be subject to further tests.
- 7 Wind load tests showed that the antenna can withstand wind speeds up to 72 Km/h.

Eutelsat s.A. Auto-Pointing Summary Sheet

**Applicant:**

HITACHI KOKUSAI ELECTRIC TURKEY
YAYINCILIK SİSTEMLERİ A.S.
Istanbul Endüstri ve Ticaret Serbest Bölgesi
Akif Kopuz Cad. No: 3 Tuzla Istanbul Turkey
Tel :+ 90 216 394 84 84
Fax :+90 216 394 84 82

Website : <http://www.hitachi-kokusai.com.tr/>
Email : Corporate.HKT@tr.hitachi-kokusai.com

Antenna model:

PDA 150 Drive News

Diameter:

1.5 m x 1.35 m

Standard:

M

Characterization date:

23-05-2017

Last test data submitted on:

21-11-2017

System Description:

Antenna system for drive-away applications. Dual offset Gregorian configuration. Single piece carbon fibre reflector 1.5 m x 1.35 m, with two port linear polarization feed manufactured by PALS trading as Hitachi Kokusai Electric Turkey Broadcasting Systems with HPA maximum permissible rating as per remark 4. ACU model: PAC 450.

Maximum Allowed EIRP: For digital carriers transmitted at the satellite receive contour of 0 dB/K (EESS 502 refers):

In the 14.00 - 14.50 GHz band:

39.9 dBW / 40 kHz for an orbital separation from the adjacent satellite $\geq 1.5^\circ$

44.9 dBW / 40 kHz for an orbital separation from the adjacent satellite $> 2.0^\circ$

In the 13.75 - 14.00 GHz band:

37.2 dBW / 40 kHz for an orbital separation from the adjacent satellite $\geq 1.5^\circ$

42.4 dBW / 40 kHz for an orbital separation from the adjacent satellite $> 2.0^\circ$

Tx Frequency:

13.75 - 14.50 GHz

Rx Frequency:

10.70 - 12.75 GHz

Pointing error:

$\leq 0.4^\circ$

Polarization error:

$\leq 2.0^\circ$

Tx XPD:

≥ 30 dB within -1 dB contour

Rx XPD:

≥ 29 dB within -1 dB contour

Remarks:

- 1 Auto-pointing tests were performed via satellite from Aflenz with the ERS of Aflenz on the 19-20 April 2017. RF performance tests were performed on three antenna unit at the at the CTS (Cobham Technical Services) test range in Leatherhead, UK, on the 24-27 November 2014.
- 2 The PDA 150 ACU auto-pointing system has been validated with three different Eutelsat satellites, with angles of the polarization plane equal to 3.5° .
- 3 Transmission is not authorized until the peaking process is completed.
- 4 The PDA 150 is authorized to operate with 1+1 HPAs with a power up to 400 W.
- 5 Any change to the characterized configuration need to be notified to Eutelsat and may be subject to further tests.

**Applicant:**

SATMISSION
Bultenvägen 5
952 61 Kalix,
SWEDEN

Tel : +46 923 137 10
Mob: +46 70 3206567
Website : www.satmission.com
Email : urban.gustavsson@satmission.com

Antenna model:

SMP 155 DA

Antenna aperture dimensions:

1.54 m H x 1.39 m V

Standard:

M

Characterization date:

26-06-2018

Validity period:

See Remark 5

Last test data submitted on:

12-10-2017

System Description:

Antenna system for drive-away applications. Dual offset Gregorian configuration. Single piece carbon fibre reflector, with two port linear polarization feed, manufactured by Satmission with HPA maximum permissible rating as per remark 4. ACU manufactured by RCI model RC4000.

Maximum Allowed EIRP: For digital carriers transmitted at the satellite receive contour of 0 dB/K (EESS 502 refers):

In the 14.00 - 14.50 GHz band:

39.6 dBW / 40 kHz for an orbital separation from the adjacent satellite $\geq 1.5^\circ$

36.1 dBW / 4 kHz (equivalent to 46.1 dBW/40 KHz) for an orbital separation from the adjacent satellite $> 2.0^\circ$

In the 13.75 - 14.00 GHz band:

37.5 dBW / 40 kHz for an orbital separation from the adjacent satellite $\geq 1.5^\circ$

44.7 dBW / 40 kHz for an orbital separation from the adjacent satellite $> 2.0^\circ$

Tx Frequency:

13.75 - 14.50 GHz

Rx Frequency:

10.70 - 12.75 GHz

Pointing error:

$\leq 0.3^\circ$

Polarization error:

$\leq 0.75^\circ$

Tx XPD:

≥ 30 dB within -1 dB contour

Rx XPD:

≥ 29 dB within -1 dB contour

Remarks:

- 1 Auto-pointing tests were performed via satellite from Kalix with the ERS of Aflenz on the 9-10 May 2017 and the 12 October 2017. RF performance tests were performed on one antenna unit at the Thales Alenia Space test range of Cannes, France on the 10 March 2017.
- 2 The SMP 155 DA ACU auto-pointing system has been validated with four different Eutelsat satellites, with angles of the polarization plane equal to 3.5° .
- 3 Transmission is not authorized until the peaking process is completed.
- 4 The SMP 155 DA is authorized to operate with 1+1 HPAs with a power up to 400 W.
- 5 This Summary's validity is subject to regular submission of patterns to confirm that the system remains compliant with measured performance at the inspection date.
- 6 Any change to the characterised configuration need to be notified to Eutelsat and may be subject to further tests.
- 7 The test campaign was performed with the antenna using a built-in inclinometer; use of the 3-axis compass is not recommended.

**Applicant:**

SATMISSION
Bultenvägen 5
952 61 Kalix,
SWEDEN

Tel : +46 923 137 10
Mob: +46 70 3206567
Website : www.satmission.com
Email : urban.gustavsson@satmission.com

Antenna model:

SMP 125 DA

Antenna aperture dimensions:

1.20 m H x 1.25 m V

Standard:

M

Characterization date:

26-06-2018

Validity period:

See Remark 5

Last test data submitted on:

07-12-2017

System Description:

Antenna system for drive-away applications. Dual offset Gregorian configuration. Single piece carbon fibre reflector, with two port linear polarization feed, manufactured by Satmission with HPA maximum permissible rating as per remark 4. ACU manufactured by RCI model RC4000. HPA model: Space Path.

Maximum Allowed EIRP: For digital carriers transmitted at the satellite receive contour of 0 dB/K (EESS 502 refers):

In the 14.00 - 14.50 GHz band:

36.7 dBW / 40 kHz for an orbital separation from the adjacent satellite $\geq 1.5^\circ$

42.2 dBW / 40 kHz for an orbital separation from the adjacent satellite $\geq 2.0^\circ$

45.3 dBW / 40 kHz for an orbital separation from the adjacent satellite $\geq 3.0^\circ$

In the 13.75 - 14.00 GHz band:

34.3 dBW / 40 kHz for an orbital separation from the adjacent satellite $\geq 1.5^\circ$

39.3 dBW / 40 kHz for an orbital separation from the adjacent satellite $\geq 2.0^\circ$

40.0 dBW / 40 kHz for an orbital separation from the adjacent satellite $\geq 2.5^\circ$

43.0 dBW / 40 kHz for an orbital separation from the adjacent satellite $\geq 3.0^\circ$

Tx Frequency:

13.75 - 14.50 GHz

Rx Frequency:

10.70 - 12.75 GHz

Pointing error:

$\leq 0.35^\circ$

Polarization error:

$\leq 1.9^\circ$

Tx XPD:

≥ 30 dB within -1 dB contour

Rx XPD:

≥ 27 dB within -1 dB contour

Remarks:

- 1 Auto-pointing tests were performed via satellite from Kalix, Sweden with the ERS of Aflenz on the 6-7 December 2017. RF performance tests were performed on one antenna unit at the Politecnico di Torino Test Range on the 22-23 November 2017.
- 2 The SMP 125 DA ACU auto-pointing system has been validated with three different Eutelsat satellites, with angles of the polarization plane equal to 3.5° .
- 3 Transmission is not authorized until the peaking process is completed.
- 4 The SMP 125 DA is authorized to operate with 1+1 HPAs with a power up to 400 W.
- 5 This Summary's validity is subject to regular submission of patterns to confirm that the system remains compliant with measured performance at the inspection date.
- 6 Any change to the characterised configuration need to be notified to Eutelsat and may be subject to further tests.
- 7 The test campaign was performed with the antenna using a built-in inclinometer; use of the 3-axis compass is not recommended.

Eutelsat s.A. Auto-Pointing Summary Sheet

**Applicant:**

DataPath International AB
Vågögatan 6 P.O. Box 1261
164 29 Kista,
SWEDEN

Tel : +46 8 728 5000
Mob: +46 703 555 424
Website : www.datapath.com
Email : mikael.borin@datapath.com

Antenna model:

CCT200 Fly-Away

Antenna aperture dimensions:

2.0 m H x 1.6 m V

Standard:

M

Characterization date:

24-06-2019

Validity period:

Temporary until 24-06-2020, see Remark 4

Last test data submitted on:

24-05-2019

System Description:

Antenna system for Fly-Away applications. Offset Gregorian configuration. Six segment carbon fibre reflector, with two port linear polarization feed, manufactured by DataPath with HPA maximum permissible rating as per remark 5.

Maximum Allowed EIRP: For digital carriers transmitted at the satellite receive contour of 0 dB/K (EESS 502 refers):

In the 14.00 - 14.50 GHz band:

41.3 dBW / 40 kHz for an orbital separation from the adjacent satellite $\geq 1.5^\circ$

46.8 dBW / 40 kHz for an orbital separation from the adjacent satellite $\geq 2.0^\circ$

46.9 dBW / 40 kHz for an orbital separation from the adjacent satellite $\geq 3.0^\circ$

In the 13.75 - 14.00 GHz band:

39.1 dBW / 40 kHz for an orbital separation from the adjacent satellite $\geq 1.5^\circ$

44.4 dBW / 40 kHz for an orbital separation from the adjacent satellite $\geq 2.0^\circ$

45.5 dBW / 40 kHz for an orbital separation from the adjacent satellite $\geq 3.0^\circ$

Tx Frequency:

13.75 - 14.50 GHz

Rx Frequency:

10.70 -12.75 GHz

Pointing error:

$\leq 0.1^\circ$

Max Polarization error:

$\leq 1.5^\circ$

Tx XPD:

>30 dB within -1 dB contour

Rx XPD:

>30 dB within -1 dB contour

G/T:

23.6 dB/K typ @ 11.85 GHz at 20° EI

Remarks:

- 1 Auto-pointing tests were performed via satellite from Kista, Sweden with the ERS of Aflenz on the 22-24 May 2019. RF performance tests were performed on one antenna unit at the Catapult in Harwell, UK on the 22-23 May 2018.
- 2 The DataPath CCT 200 ACU auto-pointing system has been validated with three different Eutelsat satellites, with angles of the polarization plane equal to 3.5°.
- 3 Transmission is not authorized until the peaking process is completed.
- 4 This temporary characterization is granted for a period of 1 year to allow DataPath to implement two S/W modifications: a) include in the ACU a DVB or closed network modem synchronization acknowledgement system to secure acquisition on the wanted satellite; b) implement Eutelsat skews look-up tables in the ACU's firmware.
- 5 The DataPath CCT200 is authorized to operate with HPAs with a power up to 400 W.
- 6 This Summary's validity is subject to regular submission of patterns to confirm that the system remains compliant with measured performance at the inspection date.
- 7 Any change to the characterised configuration need to be notified to Eutelsat and may be subject to further tests.

Eutelsat s.A. Auto-Pointing Summary Sheet

**Applicant:**

THRANE & THRANE A/S trading as COBHAM
SATCOM
Lundtoftegaardsvej 93D, 2800 Kgs.
Lyngby
DENMARK

Tel : +45 39 55 88 00

Website : www.cobham.com

Email : info@cobham.com

Antenna model:
EXPLORER 6100

Diameter:
1.0 m

Standard:
M

Characterization date:
23-01-2020

Validity period:
See remark 5

Last test data submitted on:
09-12-2019

System Description:

Antenna system based on 7 piece carbon fibre reflector, Axisymmetric 1.0 m Ku antenna, with one Tx and two Rx ports linear polarization feed, manufactured by Thrane & Thrane A/S trading as Cobham Satcom, for fly-away applications with HPA maximum permissible rating as per remark 4.

Maximum Allowed EIRP: For digital carriers transmitted at the satellite receive contour of 0 dB/K (EESS 502 refers):

In the 14.00 - 14.50 GHz band:

35.2 dBW / 40 kHz for an orbital separation from the adjacent satellite $\geq 1.5^\circ$

38.3 dBW / 40 kHz for an orbital separation from the adjacent satellite $\geq 2.0^\circ$

40.7 dBW / 40 kHz for an orbital separation from the adjacent satellite $\geq 2.5^\circ$

In the 13.75 - 14.00 GHz band:

33.5 dBW / 40 kHz for an orbital separation from the adjacent satellite $\geq 1.5^\circ$

36.8 dBW / 40 kHz for an orbital separation from the adjacent satellite $\geq 2.0^\circ$

39.2 dBW / 40 kHz for an orbital separation from the adjacent satellite $\geq 2.5^\circ$

Tx Frequency:
13.75 - 14.50 GHz

Rx Frequency:
10.70 - 12.75 GHz

Pointing error:
 $\leq 0.1^\circ$

Polarization error:
 $\leq 3.5^\circ$

Tx XPD:
 ≥ 25.0 dB within -1 dB contour

Rx XPD:
 ≥ 34.1 dB within -1 dB contour

Remarks:

- 1 Auto-pointing tests were performed via satellite from Lyngby with the ERS of Aflenz on the 09 December 2019. RF performance tests were performed on one antenna unit at the Politecnico di Torino test range on the 3-5 September 2019.
- 2 The EXPLORER ACU system has been validated with three different Eutelsat satellites, with angles of the polarization plane equal to 3.5° .
- 3 Transmission is not authorized until the peaking process is completed.
- 4 The EXPLORER 6100 comes in three standard configurations: without BUC, 8 and 20W BUC. Installation of HPAs with a power >50 W is not authorized.
- 5 The Characterisation's validity is granted as far as the static system, and is subject to regular submission of patterns to confirm that the system remains compliant with the Eutelsat standard at the inspection date.
- 6 Any change to the characterised configuration need to be notified to Eutelsat and may be subject to further tests.
- 7 The transmission in the band 13.75-14.00 GHz for antennas with a diameter < 1.2 m is subject to the ITU radio regulations in force.

ANNEX 1

THE POLARISATION SKEW OF THE EUTELSAT SATELLITES USING DUAL LINEAR POLARISATION

GENERAL

The linear polarisation planes (defined as X and Y and orthogonal to each other) of most of the Eutelsat satellites are not parallel/orthogonal to the equatorial plane.

For historical reasons, the polarisation planes are inclined by an angle with respect to the equatorial plane. This angle is referenced as the polarisation skew.

This value is of fundamental importance for the following types of antennas, whenever the polarisation alignment is performed in open loop (calculated):

- Earth Stations on Vessels (ESVs)
- Satcom-On -The Move (SOTM)
- Auto-pointing antennas

If the pointing and polarisation alignment software of an antenna falling in the categories above did not take duly into account this value of skew, the polarisation discrimination achieved at the end of the alignment would suffer a major degradation with respect to the value which the antenna optics could theoretically yield, with a consequent high risk of interference to other services on the opposite polarisation and the achievable performance would not be met.

VALUE OF THE SKEW OF THE EUTELSAT SATELLITES

The reference X-polarisation is defined as that polarisation whose plane makes an angle of 93.535° in an anti-clockwise direction, looking towards the earth, about a reference vector with respect to a plane containing this vector and the pitch axis. The reference vector is defined as the vector from the satellite in the direction 0.21° towards west and 6.07° towards north in satellite coordinates.

The reference Y-polarisation is defined as that polarisation whose plane is orthogonal to the X-polarisation plane and the reference vector defined above.

In other words the skew of the Eutelsat satellites is **$+3.535^\circ$, clock-wise** when looking at the satellite from the earth, from anywhere on the meridian (**in the northern hemisphere**) corresponding to the orbital location of the satellite.

In the southern hemisphere the skew of the Eutelsat satellites is **$+183.535^\circ$, clock-wise**, from anywhere on the meridian corresponding to the orbital location of the satellite.

There are six satellites of the Eutelsat fleet using linear polarisation which make exception.

These are:

Sesat2,
AB3,
Express A3,
Telstar 12.

for which the skew is 0.0°

and

Telecom 2 C and Telecom 2 D

for which the skew is -22° , when looking at the satellite from the earth.

EUTELSAT SATELLITES USING DUAL CIRCULAR POLARISATION

To provide additional guidance to the development of automatic pointing and polarization alignment systems of antennas, it must be noted that Eutelsat operates part of the payload capacity of the following satellites:

AB3

W4

in dual circular polarisation

and part of the payload capacity of:

Telstar-12

in left hand circular polarisation